



# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.



# U.S. Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

<b>IDENTITY: VITAMIN A&amp;D OINTMENT</b> Ingredients: Petrolatum, Wax, Lanolin. Vitamins.	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
-----------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------

## Section I

Company Name H&H LABORATORIES INC.	Emergency Telephone Number 718-624-8041
Address) 61 FOURTH STREET	Telephone Number for Information 718-624-8041
BROOKLYN, N.Y. 11231	Date Prepared 12-28-2007
	Signature of Preparer ( <i>optional</i> )

## Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%( <i>optional</i> )
None				

## Section III - Physical/Chemical Characteristics

Boiling Point	650°F	Specific Gravity (H <sub>2</sub> O = 1)	0.870
Vapor Pressure (mm Hg.)	<1	Melting Point	39.0° C
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	<1
Solubility in Water INSOLUBLE IN WATER, MISIBLE IN MIN.OIL			
Appearance and Odor Yellow/White/Opaque semi-solid, with little or no odor			

### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) APP.400° F	Flammable Limits	LFL N/AV	UFL N/AV
Extinguishing Media CARBON DIOXIDE, DRY CHEMICALS,OR FOAM			
Special Fire Fighting Procedures DO NOT USE STREAMS OF WATER AS THIS WILL SCATTER THE LIQUID AND SPREAD THE FIRE. A WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. MAY CREATE DENSE SMOKE DURING COMBUSTION.			
Unusual Fire and Explosion Hazards: MAY CAUSE DENSE SMOKE DURING COMBUSTION			

(Reproduce locally)

OSHA 174, Sept. 1985

### Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable X		N/AP
Incompatibility ( <i>Materials to Avoid</i> )OXIDIZING AGENTS			
Hazardous Decomposition or Byproducts N/AP			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

### Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
Health Hazards ( <i>Acute and Chronic</i> ) NOT CONSIDERED A PRIMARY SKIN OR EYE IRRITANT.NOT TOXIC BY ORAL INGESTION			
carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?

Signs and Symptoms of Exposure: NONE

Medical Conditions

Generally Aggravated by Exposure: NONE

Emergency and First Aid Procedures: NOT NEEDED

### Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

SMALL SPILLS MAY BE ABSORBED WITH SAND OR OTHER SUITABLE OR ABSORBING MATERIAL. IF MATERIAL SOLIDIFIES, SCRAPE INTO PERMISSIBLE DISPOSAL CONTAINERS

Waste Disposal Method

MAY BE DISPOSED OF IN AN APPROVED LANDFILL

Precautions to Be taken in Handling and Storing

STORE AT ROOM TEMPERATURE

Other Precautions: NONE

### Section VIII - Control Measures

Respiratory Protection (*Specify Type*)

NONE REQUIRED

Ventilation

Local Exhaust

Special

Mechanical (*General*)

Other

Protective Gloves NOT NECESSARY

Eye Protection NOT NECESSARY

Other Protective Clothing or Equipment NOT REQUIRED

Work/Hygienic Practices

Store at room temperature